

Sec. 1. 1	AUTHOR: Zhukovskiy, V. Ye.
	ORG: none
	TITLE: OKB-924, induction installation
	SOURCE: Ref. zh. Metallurgiya, Abs. 128106
	REF SOURCE: Elektrotermiya. Nauchno-tekhn. eb., vyp. 44, 1965, 11-12
	TOPIC TAGS: pipe, metal heat treatment, heating engineering, induction hardening, welding technology
	TRANSLATION: In 1964, the Azerbaydzhan Pipe Rolling Pignt imeni
+	V. I. Lenin began using type OKB-924 induction units developed by the Special Design Bureau of the All-Union Scientific Research
	Institute of Electrical Heating Equipment. These installations
	are part of the plant equipment in the section for production of drill pipes and are used for heat treatment of joints after weld-
	ing the end couplers to drill pipes (on a butt welder) A sche-
	matic diagram and the technical characteristics of the UKB-924
- 1	
	SUB CODE: 13

Cont 1/2

CC NR AP6030708	SOURCE CODE: UR/0368/6	36/005/002/0133/0137
AUTHOR: Burakov. V.	S.; Zhukovskiy, V. V.; Naum	enkov. P. A.: Yankovskiy.
A. A.	constant and the state of the s	
		36
DRG: none		
Prot D. Incontinution o	f atomic abgoration exacts of	
	f atomic <u>absorption spectra</u> of layers separate in space	an electric discharge with
SOURCE: Zhurnal prik	ladnoy spektroskopii, v. 5, no.	2, 1966, 133-137
tan di dia manana di Afrika. Manana di Afrika di	회사들이 많아 내려를 걸었다.	
	pectrum, absorption spectrum	, pulse discharge, spectral
line, oscillation strengt	" [발표 : [
ARSTRACT. A simple	method is described for obtain	ng atomic absorption spectra
	scharge. Possibilities are ana	
tions of the results in s	pectral analysis and for detern	nining the relative oscillator
	ines. Orig. art. has: 2 figure	
authors' abstract]		e la
SUB CODE: 03/ SUBN	M DATE: 27Aug65/ ORIG REF	: 009/ OTH REF: 004/
	The state of the s	
		一点讲话,只是就是一个女子, "我们是我们的事情,我
ard 1/1 hs	UDC: 535.34	

L 29679_66 EVT(m)/EWP(e) WH
ACC NR: AP6012852 SOURCE CODE: UR/0363/66/004/004/0306/0312

AUTHOR: Prishivalko, A. P.; Burakov, V. 8.; Eliukovakty, V. V.; Kopanik, Ye. K.

ORG: none

TITLE: Investigation of losses in a resonator with non-parallel bases

SOURCE: Zhurnal prikladnoy spektroskopii, v. 4, no. 4, 1966, 306-312

TOPIC TAGS: neodymium glass, solid state laser, laser cavity, laser optics, laser and d, laser energy

ABSTRACT: In view of the fact that the radiation-power losses of a laser depend greatly on the adjustment of the resonator mirrors, the authors analyze in detail, both theoretically and experimentally, the dependence of the laser parameters on the angle between the mirrors. The theoretical analysis is made in the geometric-optics approximation and is based on a calculation of laser resonator losses published by B. I. Stepanov and V. P. Gribovskiy (UFN v. 82, 201, 1964). A formula is derived for the loss coefficient of the mode with the largest number of passages of the beam, and is used to calculate the loss coefficient of a neodymium-glass laser. The results of the calculation were checked experimentally for three samples of neodymium-glass with different diameters and different surface finishes,

Card 1/2

UDC: 621.375.9

L 296 79-66 ACC NR: AF601285					lenge v	2 ENI	
sing a measuremen 965). This metho he characteristic elative loss coef lignment angle of apidly with incre	d is based on rise time of ficient and t the mirrors.	determining the lasing he relative The calcu	g the interraction. Plaction. Plaction polynomials in the control of the control	nal losses lots are p ower again w that the	resented est the man losses	laser from of the is- increase	
e neglected is ~l ion. The discrep n the rods, causi cademician AN BSS he results. Orig	5.5", which i ancy is attri ng deflection R B. I. Stepa	s lower that buted to the of the bear now for int	n that given e presence of ms to one si erest in the	n in the p of systems ide. The e work and	published atic inhoral authors	specifica mogeneitie thank	8
e neglected is ~l ion. The discrep n the rods, causi cademician AN BSS	5.5", which is ancy is attring deflection R B. I. Stepa art. has:	s lower that buted to the of the bear now for int figures a	n that given e presence of ms to one si erest in the nd 10 formula	n in the pof systems ide. The ework and las.	published attic inhors authors a discu	specifica mogeneitie thank ssion of	8
e neglected is ~l ion. The discrep n the rods, causi cademician AN BSS ne results. Orig	5.5", which is ancy is attring deflection R B. I. Stepa art. has:	s lower that buted to the of the bear now for int figures a	n that given e presence of ms to one si erest in the nd 10 formula	n in the pof systems ide. The ework and las.	published attic inhors authors a discu	specifica mogeneitie thank ssion of	8

EWP(e)/EWT(m)/EWP(t)/ETI AP6031745 08399-67 JP(c) JP/W/JG/WH SOURCE COLE: UR/0072/65/000/007/0011/0014 ACC NRI AUTHOR: Shumitskaya, L. F.; Gegelashvill, V. K.; Zhukovskiy, V. V.; Svidzinskaya, I.V. ORG: Ordzhonikidze Plant of Container Glassware and Glass Insulators (Ordzhonikidsav skiy steklotarno-izolyatornyy zavod) TITIE: Production of glasses stable to the action of alkali metal wapors SOURCE: Steklo i keramika, no. 7, 1966, 11-14 TOPIC TAGS: borate glass, aluminophosphate glass, sodium, cesium ABSTRACT: As a result of studies of aluminoborate and aluminoborophosphate glass systems, carried out at NIIES, S50-1 glasses stable to the action of cesium vapor and \$50-2 glasses stable to the action of sodium vapor were developed. The founding and processing technology worked out by NIIES has been used at the Ordzhonikidze Plant since 1963. Physicochemical and other properties of 550-1 and 550-2 glasses are reviewed. The furnaces used for founding the glasses and the schedules employed are described. The adoption of production of glasses resistant to alkali metal vapors has permitted the Moscow Electric Lamp Plant (Moskovskiy elektrolsmpovyy zavod) to manufacture highly economical sodium vapor illumination lamps and sodium and cesium vapor spectral lamps. Orig. art. has: 4 figures and 2 tables. SUB CODE: 11/ SUBM DATE: none/ ORIG REF: 001 Card 1/1 afs UDC: 666.117.4

L 08357-67 EWT(1)

AR6028132

BOURCE CODE: UR/0058/66/000/005/D033/D034

1

AUTHOR: Burakov, V. S.; Zhukovskiy, V. V.; Naumenkov, P. A.; Yankovskiy, A. A.

TITLE: Investigation of atomic absorption spectra of an electric discharge with spatially separated emitting and absorbing layers

SOURCE: Ref. zh. Fizika, Abs. 5D235

REF. SOURCE: Tr. Komis. po spektroskopii AN SSSR, v. 2, vyp. 1, 1964, 478-483

TOPIC TAGS: absorption spectrum, atomic spectrum, electric dischurge, gas discharge spectrosocopy

ABSTRACT: A method is proposed for obtaining atomic absorption spectra, based on the spatial separation of the same electric discharge into absorbing and emitting layers. Unlike the existing methods of atomic absorption analysis, the proposed method ensures the production of atomic absorption lines with high excitation energy. A study is made of the influence of the discharge parameters and of the method of introducing the substance in the discharge on the character of the spectrum. The possibility is discussed of using the obtained discharge to measure the relative probabilities of the transitions and to solve analytic problems. [Translation of Abstract]

SUB CODE: 20

Card 1/1 nst

ZHUKOVSKIY, YA. , Prof.

Russia - Economic Conditions.

Care of the welfare of the people is the highest law of the Lenin-Stalin party. soiuzy 8, no. 3, 1953.

Monthly List of Russian Accessions, Library of Congress, June 1953. Unclassified.

ZHUKOVSKIY, Yakov Mikhaylovich, prof.; KURINA, Ye.A., red.; STRELETSKIY, I.A., tekhn.red.

[Material and industrial basis of socialism] Material'no-proizvod-stvennaia baza sotsializma. Moskva, Izd-vo "Zmanie," 1958, 47 p.

(Vsesoiuznos obshchestvo po rasprostraneniiu politicheskikh i nauchnykh:znanii. Ser.3, no.8)


(MIRA 11:6)


(Russia—-Monomic conditions)


CHUKHNO, A.A.; KOZLOV, G.A.; KASHCHENKO, A.I.; AGANHEGTAN, A.G.; VOLKOV, M.I.; ZHUKOVSKIY, Ya.M.; NAGORNYY, A.F.; TSAGOLOV, N.A.; KOVALEVA, M.F.; PAVLOV, P.M.; ATLAS, M.S.; KATS, A.I.; NAROVLYANSKIY, N.G.; ANCHISHKIN, I.A., SPIRIDONOVA, N.S.; KRONROD, Ya.A.; SULIMOV, I.A.; BREGEL', E.Ya.; ROZENMAN, Ye.S.; VARTANYAN, K.A.; NOVIKOV, V.A.; GATOVSKIY, L.M.

Structure and content of the course on the economics of socialism. Vop. ekon: no.6:57-143 Je '62. (MIRA 15:6)

1. Kiyevskiy gosudarstvennyy universitet (for Chukhno). 2. Vysshaya partiynaya shkola pri TSentral'nom komitete Kommunisticheskoy partii Sovetskogo Soyuza (for Kozlov, Volkov, Zhukovskiy). 3. Yaroslavskiy gosudarstvennyy pedagogicheskiy institut (for Kashchenko, Narovlyanskiy, Sulimov). 4. Institut ekonomiki i organizatsii promyshlennogo proizvodstva Sibirskogo otdeleniya AN SSSR (for Aganbegyan). 5. Institut povysheniya kvalifikatsii prepodavateley obshchestvennykh nauk pri Kiyevskom gosudarstvennom universitete (for Nagornyy). 6. Moskovskiy gosudarstvennyy universitet (for TSagolov, Spiridonova). 7. Akademiya obshchestvennykh nauk pri TSentral'nom komitete Kommunisticheskoy partii Sovetskogo Soyuza (for Kovaleva), 8. Leningradskiy finansovo-ekonomicheskiy institut (for Pavlov). 9. Moskovskiy finansovyy institut (for Atlas). 10. Nauchno-issledovatel skiy institut truda (for Kats). 11. Institut ekonomiki AN SSSR (for Anchishkin, Kronrod). 12. Moskovskiy ekonomiko-statisticheskiy institut (for Bregel'). 13. Moskovskiy energeticheskiy institut (Continued on next card)







ZHUKOVSKIY, Ye.A. Some data on late results of so-malled essential hematuria. Urologiia 28 no.5:15-18 S-0'63 (MIRA 17:4) 1. Iz kafedry (zav. - prof. M.N. Zhukova) urologii Leningrad-skogo instituta usovershemstvovaniya vraohey.

TITLE: New y-flaw detectors (1) SOURCE: Defektoskopiya, no.01, 1966, 42-48 TOPIC TAGS: nondestructive testing, nondestructive quality control, flaw detector, gamma flaw detector ABSTRACT: The satisfactory performance of Soviet rockets, atomic submarines, new types of aircraft, and thousands of kilometers of gas mains has been made possible for the most part by extensive use of nondestructive testing methods, and nondestructive-testing methods, those based on the use of y-radiation are particularly significant. The y-flaw detectors are simple, reliable, mobile, self-contained, and compact. They can be used under field conditions and in compested areas. Cobalt-60, cesium-137, iridium-192, thulium-170, and selenium-75 are the most widely used sources of y-radiation. The Council for Mutual Assistance of Socialist Countries divided the general-purpose y-flaw detectors, RID, into three classes, each for a certain range of material thicknesses. Each class is divided into types according to the type and size of the radiation source (see Table 1). The Soviet Union is a leader in the development and manufacture of y-flaw detectors. However, all the existing types	ACC NR: AP6010273 DIAAP	SOURCE CODE: UR/O	381/66/000/001/0042/0048
TITLE: New \(\gamma\) -flaw detectors \(\lambda\) 1966, 42-48 TOPIC TAGS: nondestructive testing, nondestructive quality control, flaw detector, gamma flaw detector ABSTRACT: The satisfactory performance of Soviet rockets, atomic submarines, new types of aircraft, and thousands of kilometers of gas mains has been made possible for the most part by extensive use of nondestructive testing methods, and nong the nondestructive-testing methods, those based on the use of \(\gamma\)-rediation are particularly significant. The \(\gamma\)-flaw detectors are simple, reliable, mobile, self-contained, and compact. They can be used under field conditions and in competted areas. Cobalt-60, cesium-137, iridium-192, thulium-170, and selenium-75 are the most widely justed sources of \(\gamma\)-radiation. The Council for Mutual Assistance of Socialist Countries divided the general-purpose \(\gamma\)-flaw detectors, RID, into three classes, each for a certain range of material thicknesses. Each class is divided into types according to the type and size of the radiation source (see Table 1). The Soviet Union is a leader in the development and manufacture of \(\gamma\)-flaw detectors. However, all the existing types	AUTHOR: Sul'kin, A. G.; Mayorov,	A. N.; Zhukovskiy, Ye. A.	
SOURCE: Defektoskopiya, no. 1, 1966, 42-48 TOPIC TAGS: nondestructive testing, nondestructive quality control, flaw detector, gamma flaw detector ABSTRACT: The satisfactory performance of Soviet rockets, atomic submarines, new types of aircraft, and thousands of kilometers of gas mains has been made possible for the most part by extensive use of nondestructive testing methods, μ, Among the nondestructive-testing methods, those based on the use of γ-iadiation are particularly significant. The γ-flaw detectors are simple, reliable, mobile, self-contained, and compact. They can be used under field conditions and in compested areas. Cobalt-60, cesium-137, iridium-192, thulium-170, and sclenium-75 are the most widely used sources of γ-radiation. The Council for Mutual Assistance of Socialist Countries divided the general-purpose γ-flaw detectors, RID, into three classes, each for a certain range of material thicknesses. Each class is divided into types according to the type and size of the radiation source (see Table 1). The Soriet Union is a leader in the development and manufacture of γ-flaw detectors. However, all the existing types	ORG: none		
TOPIC TAGS: nondestructive testing, nondestructive quality control, flaw detector, gamma flaw detector ABSTRACT: The satisfactory performance of Soviet rockets, atomic submarines new types of aircraft, and thousands of kilometers of gas mains has been made possible for the most part by extensive use of nondestructive testing methods, among the nondestructive-testing methods, those based on the use of γ-radiation are particularly significant. The γ-flaw detectors are simple, reliable, mobile, self-contained, and compact. They can be used under field conditions and in conjected areas. Cobalt-60, cesium-137, iridium-192, thulium-170, and selenium-75 are the most widely used sources of γ-radiation. The Council for Mutual Assistance of Socialist Countries divided the general-purpose γ-flaw detectors, RID, into three classes, each for a certain range of material thicknesses. Each class is divided into types according to the type and size of the radiation source (see Table 1). The Soriet Union is a leader in the development and manufacture of γ-flaw detectors. However, all the existing types	TITLE: New y-flaw detectors \		
ABSTRACT: The satisfactory performance of Soviet rockets, atomic submarines, new types of aircraft, and thousands of kilometers of gas mains has been made possible for the most part by extensive use of nondestructive testing methods, γ Among the nondestructive-testing methods, those based on the use of γ-radiation are particularly significant. The γ-flaw detectors are simple, reliable, mobile, self-contained, and compact. They can be used under field conditions and in compessed areas. Cobalt-60, cesium-137, iridium-192, thulium-170, and selenium-75 are the most widely used sources of γ-radiation. The Council for Mutual Assistance of Socialist Countries divided the general-purpose γ-flaw detectors, RID, into three classes, each for a certain range of material thicknesses. Each class is divided into types according to the type and size of the radiation source (see Table 1). The Soviet Union is a leader in the development and manufacture of γ-flaw detectors. However, all the existing types			
types of aircraft, and thousands of kilometers of gas mains has been made possible for the most part by extensive use of nondestructive testing methods, and he nondestructive-testing methods, those based on the use of γ-radiation are particularly significant. The γ-flaw detectors are simple, reliable, mobile, self-contained, and compact. They can be used under field conditions and in congested areas. Cobalt-60, cesium-137, iridium-192, thulium-170, and selenium-75 are the most widely used sources of γ-radiation. The Council for Mutual Assistance of Socialist Countries divided the general-purpose γ-flaw detectors, RID, into three classes, each for a certain range of material thicknesses. Each class is divided into types according to the type and size of the radiation source (see Table 1). The Soviet Union is a leader in the development and manufacture of γ-flaw detectors. However, all the existing types	TOPIC TAGS: nondestructive testi gamma flaw detector	ng, nondestructive quality	control, flaw detector,
Cord 1/3 UDC: 620.179.152	types of aircraft, and thousands for the most part by extensive us nondestructive-testing methods, t significant. The γ-flaw detector compact. They can be used under cesium-137, iridium-192, thulium-of γ-radiation. The Council for the general-purpose γ-flaw detect range of material thicknesses. E	of kilometers of gas mains e of nondestructive testing hose based on the use of yes are simple, reliable, mot field conditions and in con-170, and selenium-75 are t Mutual Assistance of Social ors, RID, into three class ach class is divided into the urce (see Table 1). The Social of y-flay detectors. However	methods., Among the methods., Among the sediation are particularly file, self-contained, and pested areas. Cobalt-60, it most widely used sources ist Countries divided in, each for a certain ypes according to the priet Union is a leader in er, all the existing types

	Table 1. Ge	mma-flev	detec	tors	mn		
. 화려 하기 경기는 그런 그렇다. 1일 중에 없는 19 15 15 15 15 15 15 15 15 15 15 15 15 15	Designation	Class	Туре	Radiation	-	iess tinge, m	
				source	Steel	Light alloys	
	RID-11		1		115	5150	
	RID-12	7	Ž.	Thulium-170	115	5-1-150	非国际 [1]
	RID-21	2	ì	Ceslum-137	10-80	.50300	
	RID-22	2	2	Cesium-137	10-80	50300	
	RID-31	4	1	Cobalt-60	60-200		
	RID-32	3	2	Cobalt-60	60-200	\$1. \$1. \$1. \$2. \$4. \$4. \$4. \$1. \$1. \$1. \$1. \$1. \$1. \$1. \$1. \$1. \$1	
	RID-33	3	3	Cobalt-60	60-200	3 ★ ** *** *** *** ** ** ** ** ** ** *** *** ***	
tectors suppl sources, as w Only recently several flaw ance of Socia for use under can be used f	ied by the Mo ith the GD de the All-Union detectors in list Countrie widely varyi	srentgen tectors n Resear accordan s. The ng condi light-al	Plant, made by ch Inst ce wit first c tions f	the Experimitute of Rad h directives one to be lot rom laborato tions with r	pped wit ental pl iation E of the -produce ry to fi espectiv	ith the GUP-line handstandard result interesting has council for Mutaine RID-21 and This determine thicknesses u	ediation in Riga. developed unl Assist- , interded ctor p to

1 21844-66 ACC NR: AP6010	273										3 60	t na
pipeline welds design stage.	OLIE. err.		aldalfef -		all Marin	用海岸出来	2 an	a Ri	D-33	, are	מ	7
SUB CODE: 13/	SUBM DATE:	04Nov65/	ATD 1	PRESS:	422							
			相事人						i hi			


Automatic control system for brakes of multiple-unit train sections. Trudy MIIT no.128:92-100 '60. (MIRA 13:7) 1. Mekhanicheskiy fakul tet. Moskovskogo instituta inshenerov shelesnodorozhnogo transporta. (Automatic control)	ZHUKOVS	KIY, Ye.G., student	t 5-go kursa					
zheleznodorozhnogo transporta.		Automatic control tions. Trudy MIIT	system for b	rakes of m	ultiple-w	nit trai (MIRA	13:7)	
		zheleznodorozhnogo	transporta.			-	rov	

HELYAIV, SKI, Y. E. T.

BELYAIV, Anatoliy Ivanovich, professor, doktor; EMENAGE Anatoliy Ivanovich, professor, doktor; retsensent; professor, retsensent; GUS'KOV, V.M., professor, doktor, retsensent; TSARKGCEODYSKY, L.D., dotsent, retsensent; HALHIY, P.V., dotsent, retsensent; GUSAKOVSKIT, V.K., dotsent, retsensent; CHERNOV, A.N., redaktor; ATTOPOVICH, M.K., tekhnicheskiy redaktor

[Metallurgy of light metals; general course] Metallurgiia legkikh metallov; obshchii kurs. 4-e isd. Moskva, Gos. nauchno-tekhn. isd-vo lit-ry chernoi i tsvetnoi metallurgii, 1954, 403 p. (MIRA 7:10)

(Light metals—Metallurgy)



ZHUKOVSKIY, Ye.I., prof.; BELYAYEV, A.I., prof.; KUZNETSOV, S.I., dots.

Concerning the review of the book by V.A. Mazel' "Alumina production,"

"Evet. met. 30 no.11:82 N '57.

1. Zaveduyushchiy kafedroy "Metallurgiya legkikh metallov" SeveroKavkazskogo gorno-metallurgicheskogo instituta (for Zhukovskiy). 2. Eaveduyushchiy kafedroy "Metallurgiya legkikh metallov" Moskovskogo instituta tsvetnykh metallov i zolota im. M.I. Kalinina (for Belyapev).

3. Zaveduyushchiy kafedroy "Metallurgiya legkikh metallov" Ural'skogo
politekhnicheskogo instituta im. S.M. Kirova (for Kuznetsov).

(Alumina) (Mazel', V.A.)

A de la la companya de la companya d 80V/149-58-4-24/26 Zhukovskiy, Ye. I AUTHOR: Aluminium Works 25 Years of the Dnepr (Dvadtsatipyatiletiye Dneprovskogo alyuminiyevogo zavoda) TITLE: PERIODICAL: Izvestiya Vysshikh Uchebnykh Zavedeniy, Tsvetnaya Metallurgiya, 1958, Nr 4, pp 109-180 (USSE) ABSTRACT: When, soon after the end of World War I, plans were made for the establishment of an aluminium industry in the USSR, the task facing the Russian metallurgists was a difficult one, since the only bauxite ore deposits known at that time (i.e. the Tikhvin deposits discovered in 1916) were of such low grade that in the opinion of foreign experts they were not worth exploiting. However, already in 1915 a method of producing pure alumina from high silica content ores was patented by the present author who had developed it working in cooperation with Professor A. N. Kuznetsov. (A similar method, known as the Pedersen process, was patented abroad at a much later date and is still being used in Norway, at the Hoyanger plant). The laboratory trials of the new, electro-thermic process were completed in 1928 and gave so promising Card 1/3 results that in the same year a special development plant


SOV/149-58-4-24/26 Aluminium Works 25 Years of the Dnepr was constructed at the Tsaritsin Works, where standard quality alumina was produced in 1929. At the same time, a part of another (Krasnyy Vyborzhets) works was converted to serve as a development unit in which the first batch of metallic aluminium was produced in 1929. Following the satisfactory completion of the exploratory work, a decision to build the Dnepr and Volkhov aluminium combines was made in August, 1929. a number of large scale production problems, a large development plant was first built in Leningrad in 1929. The construction work on the Daepr plant was started in 1930 and the first batch of metallic aluminium was produced in January, 1933. During the first years of operation the equipment and the production techniques were continuously improved. The electrolytic cells were enlarged from 25 000 to 35 000 amp capacity and continuous anodes, later adopted in all other aluminium plants, were introduced. The Deepr works was completely destroyed during World War II. In rebuilding it, use was made of all the latest developments in the Later, the manufacturing Card 2/3 aluminium production techniques.


25 Years of the Dnieper Aluminium Works

SOV/149-58-4-24/26

process was improved still further by introduction of continuous decomposition of the aluminate solutions in air agitated & interpretation of the aluminate solutions in possible to make the process completely automatic. Development of a new composition electrolyte made it possible to obtain higher yield per power unit, to increase the current density and yet to minimise the power losses by reducing the number of undesirable anode effects.


Card 3/3






Inst	itutions	Nutrition grees in S) Moscow V	eceranari	, nead of		in of Hi	gher Edu	cation (.55K, 1.09	CO#, 1750
S0:		ya Letopis								
*	For Degr	ee of Cand	lidate in	Agricul	tural S	ciences				

ZHUKOVSK	IY. Ye.P. kn	ndidat sel'sk	okhozys	ystvenny	kh nauk.			
	Determining in intensive Trudy VNIIK	the food val e fattening o 3:140-168 5	ue of r f swine 6.	ations a on modi	nd consump fied lard-	making r	nutrients rations A 10:4)	
		(SwineFeedi	ng am	Isading	REUTINA			





SHAPIRO, Ye.A.; ZHUKOVSKIY, Ye.S.; MUSTAPABHKOVA, A.A.; HIKHAYLOV, H.D.; KOBYLYANSKIY, A.L.; KOHONYKHIN, A.G.; KPSHTHIN, R.R.; KARPINSKIY, V.F.; DAVYDOVA, R.T.; TROITSKIY, V.I., red.; GOR'KOVA, A.A., vedushchiy red.; FEDOTOVA, I.G., tekhn.red.

[Establishing standards for material consumption and stocks in the petroleum industry] Normirovanie raskhoda i proisvodstvennykh zapasov osnovnykh materialov v neftianci promyshlennosti. Moskva, Gos.nauchno-tekhn.izd-vo neft. i gorno-toplivnoi lit-ry, 1959.
252 p. (MIRA 12:12)

(Petroleum industry--Standards)

BERZON, O.F., inzh.; BUKSHTEYN, D.I., inzh.; KUPERMAN, Ya.M., kand. ekon. nauk; RUDNER, I.B., kand. tekhn.nauk; GORBUSHIN, P.B., red.; ZHUKOVSKIY, Ye.S., nauchn. red.; GIROVSKIY, V.F., glav. red. serii; BOGINA, S.L., red.; GOL BERG, T.M., tekhn.red.

[Handbook on material and machinery supply for construction units] Spravochnoe posobie po material no-tekinicheskomu snabzheniiu stroitel nykh organizatsii. Pod obshchei red. P.B.Gorbushina i D.I.Bukshteina. Moskva, Gosstroiizdat, 1963. 607 p. (MIRA 17:1)

1. Moscow. Nauchno-issledovatel'skiy institut ekonomiki stroitel'stva. 2. Direktor Nauchno-issledovatel'skogo instituta ekonomiki stroitel'stva i chlen-korrespondent Akademii stroitel'stva i arkhitektury (for Gorbushin). 3. Rukovoditel'otdela normirovaniya material'nykh resursov i tsen na stroitel'nye konstruktsii nauchno-issledovatel'skogo instituta ekonomiki stroitel'stva (for Bukshteyn).

(Construction industry-Management)

ि के के के के कि अपने के किए किए

ZHUKOVSKIY, Yefim Semenovich; IVANOV, Nikolay Vasil yevich, kard. ekon. nauk; KUPERMAN, Yakov Mironovich, kard. ekon. nauk; Prinimal uchastiye EUKSHTEYN, D.I.; VARENIK, Ye.I., prof., doktor tekhn. nauk, retsenzent; OCNEVAYA, N.V., kard. ekon. nauk, st. prepod., retsenzent; USPENSKIY, V.V., kard. ekon. nauk, retsenzent; VERESHCHAGINA, V.Ya., red.

[Organization of procurement in construction] Organizatsia snabzheniia stroitel stva. Moskva, Vysahaia shkola, 1965.
283 p. (MIRA 18:8)

1. Zaveduyushchiy kafedroy "Ekonomiki i organizatsii stroitel'stva" Moskovskogo inzbenerno-skonomicheskogo instituta im. S.Ordzhonikidze (for Varenik). 2. Kafedra "Ekonomiki i organizatsii stroitel'stva" Moskovskogo inzbenerno-ekonomicheskogo instituta im. S.Ordzhonikidze (for Ognevaya).

CIA-RDP86-00513R002065010016-0 "APPROVED FOR RELEASE: 07/16/2001

स्त र अहे हरू । इ.स. इ.स. प्रतिसादको अन्तरसासामा । यह यह यह । ZHUKOYSKIY, Ye. V.

Vargin, V.V., Makarov, A.V., Zhukovskiy, Ye.V.,

72-2-14/20

AUTHORS:

Nyohke, A.A.

TITLE:

The "Elektroverr" in Switzerland (Zavod "Elektroverr" v

Shveytsarii).

PERIODICAL:

Steklo i Keramika, 1958,

Nr 2, pp. 33-36 (USSR)

ABSTRACT:

The electric continuous glass melting furnace is located on the second floor of the building and is used for the production of plate glass by the Furkeau method. Dimensions and shape are shown in fig. 1. At each side of the furnace there are 6 electrodes. With a melting surface of 26 m² the glass production output amounts to 1.2 t per m² daily. The composition of the glass is that usual for the Furkeau process (14,8% sodium oxide). The layer consists of 70% raw material and 30% scrap glass, and is conveyed mechanically to the furnace without intermedia. to the furnace without interruption. The temperature regime in the smelting department of the furnace is controlled by means of a thermocouple (fig. 3). The temperature in this zone amounts to 1410°. Fig. 2 shows the burning of GO in GO2 above the electrodes along the entire width of the furnace. In the case of normal operation the temperature in the machine chamber amounts to

Card 1/2

ACC NR. AP7004651 (A, N) SOURCE CODE: UR/0432/66/600/001/0015/0016

AUTHOR: Gil'man, G. I.; Zhukovskiy, Ye. Ye.; Chugunov, K. M.

ORG: none

TITLE: System for setting limit values for parameters of the IV-500 data processing computer

SOURCE: Mekhanizatsiya i avtomatizatsiya upravleniya, no. 1, 1966, 15-16


TOPIC TAGS: FERRITE core memory, magnetic core storage, computer memory, Computer / IV-500 computer.

ABSTRACT: A non-destructive-read random-access word-organized core memory designed for the IV-500 data processing computer is described. The memory uses magnetic cores separated 4 mm from each other and rod-like permanent magnets in the plane of the cores which store "0". These magnets link the flux from the input winding and output winding separately, and thus break the coupling from input to output of the core which stores a logical zero. The information is read by full (400 to 500 mamp) current increasing the output signal to 300 mv at a S/N ratio of 15. The memory has 12 matrix plates with miniature connectors to

Card 1/2

UDC: 681.142.652.2

lecoders; (the needed	one for sele word on thi 775-bit wo	change in case ecting the requesting the requestrible req	ch 80 x 410- mum memory c	and one mm matr	ix bos	ard con	-
SUB CODE:	09/ SUBM	DATE: none/	ORIG REF:	005/	OTH 1	ref: 0	01.
Card 2/2							





ZHUKOVSKIV. V...G.; KRISTUK, E.M.; LATYSHEV, G.D.; SERMHTW, A.G.


Magnetic aftereffect in iron-core electromagnets. Izv.AN SSSR.
Sor.fiz. 20 no.3:371-373 Mr '56.

1. Kafedra fiziki Leningradekogo instituta inshenerov shelesnodoroshnogo transporta imeni V.N. Obrastsova.
(Klectromagnets)


of the prostate. Biokhimila 30 no.2;350-357 Mr-Ap '65. (MIRA 18;7) 1. Sanitarno-gigiyanicheskiy meditsinskiy institut, Leningrad.	Kine of th	tics o	f tran state.	aphosi Bioki	horyl imila	ation 30 n	unde o.2:3	r the 50-35	inf	Luenc Ap	в of 165.	acid	phosp (MIRA	hatase 18:7	;)
	 	for the second		1000				· · ·		* 1			d.		
														The second secon	
당신하는 경하는 그 눈한 사는 가게 되었다. 한 나는 구별한 분들 등에는 바람은 불일은 하신부를 때라는 것 같															










	ZHUKOVSKIY,									
2364	Char Vall	acteristics of ley. Vest. LGI	of the ge J 19 no.1	omorpholo 8:77-87	ogical s	itructur	e of th	e Olene	k 17:11)	
								Lumer	1,.11,	13.7%
										i i.







TOPIC TASS: spece of account below.



OPARIN, A.I., akadomik; STUDITSKIY, A.N., prof.; NAUMOV, N.P., prof.; KOVAL'SKIY, V.V.; YUROVA, I.L., dots.; PLATONOV,G.V., prof.; KORANOV, V.M.; FURNAN, A.Ye., dots.; NEDVEDEV, N.V., prof.; YAKINOV, V.P., kand. biol. nauk; ZHUKOV-VEKEZHRIKOY. N.N., BONDARENKO, P.P., prof.; MAYSKIY, I.N., prof.; TRIBULEY, G.P., dots.; TSAREGGRODTSEV, G.I., dots.; DOERCKHYALOV, V.P., kand. biol. nauk; YAZDOVSKIY, V.I., prof.; VIKTOROVA, V., red.; CHEREMYKH, I., mlad. red.; ULANOVA, L., tekhn.red.

[Studies on the dialectic of living nature] Ocherk dialektiki zhivoi prirody. Moskva, Sotsekgiz, 1963. 527 p. (MIRA 16:12)


1. Chlen-korrespondent Vsesoyuznoy akademii sel'skokhozyaystvennykh nauk imeni V.I.Lenina (for Koval'skiy).


2. Deystvitel'nyy chlen AMN SSSR (for Zhukov-Verezhnikov).


ZHUKOV-VEREZHNIKOV, N.N.; MAYSKIY, I.N.; PEKHOV, A.P.; RYBAKOV, N.I.;
SAKSONOV, P.P.; MISHCHENKO, B.A.; KOZLOV, V.A.; HYBAKOVA, K.D.;
ANISKIN, Ye.D.

Effect of radioprotective substances on the phage production of lysogenic bacteria induced by X-ray irradiation. Radiobiologiia (MIRA 18:4) 4 no.5:738-742 '64.

1. Institut eksperimental'noy biologii AMN SSSR, Moskva.







3 272	
E ST	L 03777-67 FSS-2/EWT(1)/EEC(k)-2/T SCIB TT/DD/JK/RD/CW SOURCE CODE: UR/0293/66/004/004/0634/0640
7	
	AUTHOR: Zhukov-Verezhnikov, N. N.; Mayskiy, I. N.; Delong, N. L.; Rybakov, N. I.; Kozlov, V. A.; Davydov, B. I.; Antipov, V. V.; Saksonov, P. P.; Rybakova, K. D.;
	Kozlov, V. A.; Davydov, B. I.; Antipov, V. V., Same
	Rozlov, V. A.; Davydov, B. I., Missey, Tribulev, G. P.
	ongs none
54 s.	TITLE: Biological investigations on the Voskhod-1 and Voskhod-2 spaceships
	4 no. 4 1966, 634-640
	TOPIC TAGS: biologic spaceflight, street, lyangente bacteria, landing, wheat seed
	TOPIC TAGS: biologic spaceflight, street, by against bacteria, land, wheat seed/ protective drug, bear aptupropylanine, spaceflight, freeting, plant of the Voskhod 2 about of the confit
	Voskhod 1 Noskhod 2 aboutroft
	The vortice were performed on the Voskhod-1 and Voskhod-2 specific (1). The
	cultures were carried in 1.5 me of the ampules contained the radioprotective disk
	I was an tour only is an interest of the contract of the contr
	Results showed that on the basis Experiments on Voskhod-2 resulted in
	carried on Voskhod-1 and the controls. Experiments on Voskhod-2 residence carried on Voskhod-1 and the controls. Experimental cultures as compared to conslightly higher viability on the part of experimental cultures carried on the two flights also did trols. Phage production of experimental cultures carried on the two flights also did trols.
	trols. Phage production of experimental turing UDC; 629.198.621:576.8
	Card 1/2

not exceed phage production of controls. Thus, it was not possible to demonstrate the protective properties of β-mercaptopropylamine. An attempt was made to determine the protective properties of β-mercaptopropylamine. Coli K-12 (λ) to consequent whether spaceflight sensitized lysogenic cultures of E. coli K-12 (λ) to consequent whether spaceflight sensitized lysogenic cultures of E. coli K-12 (λ) to consequent whether spaceflights showed that phage production in space-exposure to small doses of x-rays. Results showed that phage production in spaceflown samples was almost identical to that of the controls. In addition, air-dried flown samples was almost identical to that of the controls. In addition, air-dried flown samples was almost identical to that of the genetic effects of space-pocket during his EVA for the purpose of determining the genetic effects of space-pocket during his EVA for the purpose of determining the genetic effects of space-pocket during his EVA for the purpose of determining the genetic effects of space-pocket during his EVA for the purpose of determining the genetic effects of space-pocket during his EVA for the purpose of determining the genetic effects of space-pocket during his EVA for the purpose of determining the genetic effects of space-pocket during his EVA for the purpose of determining the genetic effects of space-pocket during his EVA for the purpose of determining the genetic effects of space-pocket during his EVA for the purpose of determining the genetic effects of space-pocket during his EVA for the purpose of determining the genetic effects of space-pocket during his EVA for the purpose of determining the genetic effects of space-pocket during his EVA for the controls. It is assumed that the absence space his effects of space-pocket during his EVA for the purpose of determining the genetic effects of space-pocket during his EVA for the controls. It is assumed that the absence space his effects of space-pocket during his EVA for the controls. It is assumed that the absence	L 03777-67							0
	not exceed phage the protective whether spacefl exposure to sma flown samples w seeds of pine a pocket during h	production properties of ight sensiti li doses of as almost id nd winter whits EVA for the Results discontinuous products discontinuous productions and winter whits EVA for the Results discontinuous productions and winter whits EVA for the results discontinuous productions are productions and productions are productions. The productions are productions are productions are product	zed lysogen x-rays. Re lentical to leat (PPG-18 the purpose id not rever	ic cultures sults showe that of the 6) were car of determin al any subs I the contro	d that phate controls. ried on Voling the gerantial different controls. It is	ge produ In add skhod-2 netic ef ferences assumed	ction in ition, ai and in Le fects of between that the	space- ir-dried conov's space- the two e absence
	of the effects plants in these flights took p	of spacefli	ght factors s is due to art. has:	on lysogen the partic 5 tables.	ular condit	. 10	ler which	these [BM]
	of the effects plants in these flights took p	of spacefli	ght factors s is due to art. has:	on lysogen the partic 5 tables.	ular condit	. 10	ler which	these [BM]

ACC NR. AT6036563

SOURCE CODE: UR/0000/66/000/000/0172/0173

AUTHOR: Zhukov-Verezhnikov, N. N.; Mayskiy, I. N.; Tribulev, G. P.; Rybakov, N. I.; Podoplelov, I. I.; Dobrov, N. N.; Antipov, V. V.; Kozlov, V. A.; Saksonov, P. P.; Parfenov, G. P.; Sharyy, N. I.

ORG: none

TITIE: Some results and trends in the study of the biological effect of cosmic radiation and dynamic flight factors using microbiological and cytological models [Paper presented at the Conference on Problems of Space Medicine held in Moscow from 24 to 27 May 1966]

SCURCE: Konferentsiya po problemam kosmicheskoy meditsiny, 1966. Problemy kosmicheskoy meditsiny. (Problems of space medicine); materialy konferentsii, Moscow, 1966, 172-173

TOPIC TAGS: manned space flight, space biologic experiment, tissue culture, lysogenic bacteria, cosmic radiation biologic effect, combined stress/Voskhod-1

ABSTRACT: Systems of lysogenic bacteria and single layer cultures of normal and cancer cells of man have been used on all spaceflights since the second orbital spaceship. This report presents the results of investigations performed on spaceships of the Vostok and Voskhod types. Biological experiments carried out on Vostok-3, -4, -5, and -6 indicate that phage production of lysogenic culture of E. coli K-12 increases with the duration of the flight. However, a direct linear relationship between the biological

Card 1/3


ACC NR: AT6036563

effect and the time of exposure in space was not established. The results obtained make it possible to assume that the biological effect in the above experiments depends on the combined effect of spaceflight factors, and specifically vibration, weightlessness, and radiation.

Ground experiments have indicated that the sensitivity of a lysogenic bacteria system to gamma irradiation (CO⁶⁰) increases if the bacteria were previously exposed to vibration. These results not only confirm this supposition but make a more differentiated approach to evaluation of various spaceflight factors possible. However, in order to obtain a more complete picture of the genetic and radiation hazard of such flights, it is necessary to consider data obtained with more highly organized biological objects. Consequently, the results of spaceflight experiments performed with single-layer cultures of somatic human cells are of definite interest. In the series of experiments carried out on Vostok-1, -2, and -4, it was found that viability, and such indices as the coefficient of proliferation, the percentage of dead cells, and the morphological, antigenic, and cultural properties of the tissues, did not differ substantially from controls which were kept at the cosmodrome or the laboratory.

Card 2/3

ACC NRI AT603656					
However, w	hen tissues wer	e subjected to a	second space	eflight	;
	ostok-6, and Vo				
	igation in the lat				
	other noticeable				
	aceflight factors Further invest				
spaceflight utili	zing lysogenic ba	igations of the carteria and tige	rorogical elle	scis Di e culturae	
	. [W.A. No. 22;			p Curtures	• 1
SUB CODE: 06, 2	2 / SUBM DATE:	00May66			
SUB CODE: 06, 2	2 / SUBM DATE:	00May66			
SUB CODE: 06, 2	2 / SUBM DATE:	00May66			
SUB CODE: 06, 2	2 / SUBM DATE:	00May66			
SUB CODE: 06, 2	2 / SUBM DATE:	00May66			
SUB CODE: 06, 2	2 / SUBM DATE:	00May66			
SUB CODE: 06, 2	2 / SUBM DATE:	00May66			
SUB CODE: 06, 2	2 / Subm date:	00May66			
SUB CODE: 06, 2	2 / SUBM DATE:	00May66			
SUB CODE: 06, 2	2 / Subm date:	00May66			




Genesis of ijolite-urtite in the Khibini Massif. Trudy IMGRE no.5:118-125 '61. (MIRA 15:7) (Khibiny Mountains—Ijolites) (Khibiny Mountains—Urtite)	ZHUK-POCI	EKUTOV, K.	A						
		Genesis of no.5:118-12 (Khibiny	ijolite-urt 25 '61. Mountains-	tite in the -Ijolites)	Khibini I	Massif. 1	Trudy IMGRI (MIRA —Urtite)	5 15:7)	


Ch'u Fang-sai goes into battle. Sov.voin 38 no.16:27-28 Ag '56. (Vietnam)	ZHUKROV	SKIY, Voytsekh	[Zuk	rowsk	1, Wo.	jciec	h],	laur	eat	Gosu	darst	vennoy		
(Yietnam)		Ch'u Fang-sai Ag '56.	goes	into	batt	lo.	Sov.	voin	38	no .1	6:27-	28 (MLR/	9:12)	
				(Viet	nam)									

ROMANTSHY, Ye	H, ZHULAHOYA. Z.I.	- Company of the Comp			
Acety	lation of sulfanilan English summary in	nide in animals i insert]. Biokhim	rradiated with liia 21 no.6:663-	Crays 667 N-D '56. (NLRA 10:7)	
	(ROZNIGEN RAYS, of	off. of x-rays in			
	on surrailiam:	de acatylation i	a rats (Aus))		

ROMANTSE	Ye. F.; ZHUIAN	OVA, Z.I.			
	(ROENTGE	araaminobensoic aci 5 no.1:10-15 Ja- F N RAYS, effects,	159。 () () () () () ()	irradiated	rats.
	(PARAANI)	PARA acetylation in NOBENZOIC ACID, meteotylation, eff. of meteorylation, eff. of meteorylation, eff.	ıb.		
			- Teys III rats	(Rus))	


			1 n	<u>U</u>		<i>)</i>								**								
	Character and Stability of 1 ⁵¹ Bood in Bone Tissue, by N. O. Raumerttly, C. L. Torthinkyn, and V. S. Mulabuba.	Effect of Complex-Forming Substances on the Moding Character of Modico stores in the Mood, by L. N. Bathitages and V. S. Balabaha	SP , T, and Ca in the Black of Radioscillys Inctopes SP , T, and Ca in the Blood, by L. M. Bacbitsqua and T. S. Balababa 117	Physicochestad (Chromtographic) Investigation of the Effectiveness of Certain Couples-Parining Substances, by L. I. Tibboors, and L. N. Babbinapa.	Constit Information	Part 2. Elimination of Endicactive Isotopes From the Organiza	Pearstilly of the Utilization of Chemical Com- pounts as Energy Tayle in the Protection from Pear- trains Rediction, by 6. Ye. Philips. 93	of Organic Perceides in the Livelines on the Fernance of Organica Perceides in the Livelines Organica, by It. B. Remarker and E. I. Balinorra.	TER	Affect of Protective Substances on Protein Sale- bydryl Groups in the Orpone and Treepes of Earlity— and Friedrick Mainals, by T. G. Tahrrier and L. S. Ingers	Effect of Protective Doses of 1-Cysteller on the Level of Respression Salinderyl Groups in the Misszes of Rate Limitated With K-Rays, by L. S. Laupone 55	On the Medhetia of the Protective Action of Some Thiel Compounts, by Y. G. Takowler and L. S. Ingers.	Existinging Steem the Structure and Properties of Salar-Containing Companies and Their Properties Action From Penetrating Reliation, by F. G. Yaboyley 1)	Present thate of Chesical Protection from Locating To Resisting, by F. S. Malababba 7	Fact 1. Chesteal Projection From Locating Hallation		3 B E E M	E 2	-tion in which the author outlines the purpose of the book, and her sections. The first section deals with the problem of the chemical protection of the organization prescribing reliable for a brief analysis is given by the organization which we consider the contract of	Limitely (Chemical Protection of the Organism From Imminist Patients), earthough by Tr. 5: Balabatha; Noscow, Absorbath; 1950, pp 1-153. Absorbath; 1950, pp 1-153.	Think him accepts or think the state of the	
					4	7						••••				The state of the s	******	de ten de si				








· · · · · · · · · · · · · · · · · · ·	
	A 4.4
	Role of Peroxides and Oxygen (Cont.) SOV/5628
	Kolomiytseva, I. K., and A. M. Kuzin [Institute of Biophysics, AS USSR]. Lipid Peroxides in a Normal and in an Irradiated
	Kuzin, A. M., L. M. Bronskaya, N. M. Berezina, and V. A. Yazykova [Institute of Hiophysics, AS USSR]. Formation of Peroxides in Gamma-Irradiated Plant Seeds
	Zhulanova, Z. I., I. A. Korovina, and Ye. F. Romantsev. Formation of Organic Peroxides in an Organism During Irradiation on an X-Ray Apparatus With a Dose Rate of 130 r/sec 43
	Zhuravlev, A. I. Role of Antioxidants in Primary Radiobiological Sreets 55
	Mikhlin, D. M. (Deceased) [Institut blokhimii im. A. N. Bakha AN SSSR - Institute of Biochemistry imeni A. N. Bakh, AS USSR]. Effect of Ionizing Radiation of Oxidation-Reduction Reactions
	Card 3/5


	Romantsev, e.f.				
Excretion condition	Excretion of descriptidine from the organism under vacconditions of irradiation. Med.rad. 5 no.3439-43 60				
	(DEOXYCYTIDINE)	(RADIATION		(MIRA	13:12)



















ACC NR: AP6018895 SOURCE CODE: UR/0237/66/000/006/0046/0046 AUTHOR: Vanyukov, M. P.; Venchikov, V. A.; Zhulay, V. Ya.; Isayenko, V. I.; CRG: none SOURCE: Optiko mekhanicheskaya promyshlennost', no. 6, 1966, 46 TOPIC TAGS: solid state laser, laser emission, neodymium glass ABSTRACT: An investigation was made of a laser in which high emission energy of the light pulse was obtained by the use of neodymium glass rods. Cylindrical specimens of glass (45 mm in diameter and 250 mm long) activated with neodymium were connected in series-parallel. Each specimen was optically pumped by six direct pulse lamps placed in a multielliptical illuminator. The laser consisted of two identical channels, each containing three rods assembled on one axis. Q-modulation was done by two prisms fixed on a common shaft rotating at 18,000 rpm. The light diameter of the prism (30 mm) was coordinated with the light diameter of the operating rod by means of a Galileian tube. The experiments showed that for effective pumping of an operating body 45 mm in diameter the content of Nd203 should not exceed 4%. In this way it is possible to obtain an amplification coefficient of one rod equal to 3 and provide a yield energy of 25—30 joules from one specimen. Connecting the rods	ACC NR. AP6018895 SOURCE CODE: UR/0237/66/000/006/0046/0046 AUTHOR: Vanyukov, M. P.; Venchikov, V. A.; Zhulay, V. Ya.; Isayenko, V. I.; BORG: none FITTLE: Two-channel single-pulse laser with an energy of 180 joules SOURCE: Optiko mekhanicheskaya promyshlennost', no. 6, 1966, 46 FOPIC TAGS: solid state laser, laser emission, neodymium glass ABSTRACT: An investigation was made of a laser in which high emission energy of the light pulse was obtained by the use of neodymium glass cofficient of glass (45 mm in diameter and 250 mm long) activated with neodymium were connected in series-parallel. Each specimen was optically pumped by six direct pulse lamps placed in a multielliptical illuminator. The laser consisted of two identical channels, each containing three rods assembled on one axis. Q-modulation was done by two prisms fixed on a common shaft rotating at 18,000 rpm. The light diameter of the prism (30 mm) was coordinated with the light diameter of the operating rod by means of a Galileian tube. The experiments showed that for effective pumping of an operating body 45 mm in diameter the content of Nd203 should not exceed 47. In this	1	29565_66
ORG: none FITTLE: Two-channel single-pulse laser with an energy of 180 joules SOURCE: Optiko mekhanicheskaya promyshlennost', no. 6, 1966, 46 TOPIC TAGS: solid state laser, laser emission, neodymium glass ABSTRACT: An investigation was made of a laser in which high emission energy of the light pulse was obtained by the use of neodymium glass rods. Cylindrical specimens of glass (45 mm in diameter and 250 mm long) activated with neodymium were connected in series-parallel. Each specimen was optically pumped by six direct pulse lamps placed in a multielliptical illuminator. The laser consisted of two identical channels, each containing three rods assembled on one axis. Q-modulation was done by two prisms fixed on a common shaft rotating at 18,000 rpm. The light diameter of the prism (30 mm) was coordinated with the light diameter of the operating rod by means of a Galileian tube. The experiments showed that for effective pumping of an operating body 45 mm in diameter the content of Nd ₂ O ₃ should not exceed 4%. In this way it is possible to obtain an amplification coefficient of one rod equal to 3 and provide a yield energy of 25—30 joules from one specimen. Connecting the rods	ORG: none TITLE: Two-channel single-pulse laser with an energy of 180 joules SOURCE: Optiko mekhanicheskaya promyshlennost', no. 6, 1966, 46 TOPIC TAGS: solid state laser, laser emission, neodymium glass ABSTRACT: An investigation was made of a laser in which high emission energy of the light pulse was obtained by the use of neodymium glass rods. Cylindrical specimens of glass (45 mm in diameter and 250 mm long) activated with neodymium were connected in series-parallel. Each specimen was optically pumped by six direct pulse lamps placed in a multielliptical illuminator. The laser consisted of two identical channels, each containing three rods assembled on one axis. Q-modulation was done by two prisms fixed on a common shaft rotating at 18,000 rpm. The light diameter of the prism (30 mm) was coordinated with the light diameter of the operating rod by means of a Galileian tube. The experiments showed that for effective pumping of an operating body 45 mm in diameter the content of Nd ₂ O ₃ should not exceed 4%. In this way it is possible to obtain an amplification coefficient of one rod equal to 3 and provide a yield energy of 25—30 joules from one specimen. Connecting the rods		
ABSTRACT: An investigation was made of a laser in which high emission energy of the light pulse was obtained by the use of neodymium glass rods. Cylindrical specimens of glass (45 mm in diameter and 250 mm long) activated with neodymium were connected in series-parallel. Each specimen was optically pumped by six direct pulse lamps placed in a multielliptical illuminator. The laser consisted of two identical channels, each containing three rods assembled on one axis. Q-modulation was done by two prisms fixed on a common shaft rotating at 18,000 rpm. The light diameter of the prism (30 mm) was coordinated with the light diameter of the operating rod by means of a Galileian tube. The experiments showed that for effective pumping of an operating body 45 mm in diameter the content of Nd ₂ O ₃ should not exceed 4%. In this way it is possible to obtain an amplification coefficient of one rod equal to 3 and provide a yield energy of 25—30 joules from one specimen. Connecting the rods	ABSTRACT: An investigation was made of a laser in which high emission energy of the light pulse was obtained by the use of neodymium glass rods. Cylindrical specimens of glass (45 mm in diameter and 250 mm long) activated with neodymium were connected in series-parallel. Each specimen was optically pumped by six direct pulse lamps placed in a multielliptical illuminator. The laser consisted of two identical channels, each containing three rods assembled on one axis. Q-modulation was done by two prisms fixed on a common shaft rotating at 18,000 rpm. The light diameter of the prism (30 mm) was coordinated with the light diameter of the operating rod by means of a Galileian tube. The experiments showed that for effective pumping of an operating body 45 mm in diameter the content of Nd ₂ 0 ₃ should not exceed 4%. In this way it is possible to obtain an amplification coefficient of one rod equal to 3 and provide a yield energy of 25—30 joules from one specimen. Connecting the rods		AUTHOR: Vanyukov, M. P.; Venchikov, V. A.; Zhulay, V. Ya.; Isayenko, V. I.; B
ABSTRACT: An investigation was made of a laser in which high emission energy of the light pulse was obtained by the use of neodymium glass rods. Cylindrical specimens of glass (45 mm in diameter and 250 mm long) activated with neodymium were connected in series-parallel. Each specimen was optically pumped by six direct pulse lamps placed in a multielliptical illuminator. The laser consisted of two identical channels, each containing three rods assembled on one axis. Q-modulation was done by two prisms fixed on a common shaft rotating at 18,000 rpm. The light diameter of the prism (30 mm) was coordinated with the light diameter of the operating rod by means of a Galileian tube. The experiments showed that for effective pumping of an operating body 45 mm in diameter the content of Nd ₂ O ₃ should not exceed 4%. In this way it is possible to obtain an amplification coefficient of one rod equal to 3 and provide a yield energy of 25—30 joules from one specimen. Connecting the rods	ABSTRACT: An investigation was made of a laser in which high emission energy of the light pulse was obtained by the use of neodymium glass rods. Cylindrical specimens of glass (45 mm in diameter and 250 mm long) activated with neodymium were connected in series-parallel. Each specimen was optically pumped by six direct pulse lamps placed in a multielliptical illuminator. The laser consisted of two identical channels, each containing three rods assembled on one axis. Q-modulation was done by two prisms fixed on a common shaft rotating at 18,000 rpm. The light diameter of the prism (30 mm) was coordinated with the light diameter of the operating rod by means of a Calileian tube. The experiments showed that for effective pumping of an operating body 45 mm in diameter the content of Nd ₂ O ₃ should not exceed 4%. In this way it is possible to obtain an amplification coefficient of one rod equal to 3 and provide a yield energy of 25—30 joules from one specimen. Connecting the rods		ORG: none TITLE: Two-channel single-pulse laser with an energy of 180 joules
ABSTRACT: An investigation was made of a laser in which high emission energy of the light pulse was obtained by the use of neodymium glass rods. Cylindrical specimens of glass (45 mm in diameter and 250 mm long) activated with neodymium were connected in series-parallel. Each specimen was optically pumped by six direct pulse lamps placed in a multielliptical illuminator. The laser consisted of two identical channels, each containing three rods assembled on one axis. Q-modulation was done by two prisms fixed on a common shaft rotating at 18,000 rpm. The light diameter of the prism (30 mm) was coordinated with the light diameter of the operating rod by means of a Galileian tube. The experiments showed that for effective pumping of an operating body 45 mm in diameter the content of Nd ₂ O ₃ should not exceed 4%. In this way it is possible to obtain an amplification coefficient of one rod equal to 3 and provide a yield energy of 25—30 joules from one specimen. Connecting the rods	ABSTRACT: An investigation was made of a laser in which high emission energy of the light pulse was obtained by the use of neodymium glass rods. Cylindrical specimens of glass (45 mm in diameter and 250 mm long) activated with neodymium were connected in series-parallel. Each specimen was optically pumped by six direct pulse lamps placed in a multielliptical illuminator. The laser consisted of two identical channels, each containing three rods assembled on one axis. Q-modulation was done by two prisms fixed on a common shaft rotating at 18,000 rpm. The light diameter of the prism (30 mm) was coordinated with the light diameter of the operating rod by means of a Galileian tube. The experiments showed that for effective pumping of an operating body 45 mm in diameter the content of Nd ₂ O ₃ should not exceed 4%. In this way it is possible to obtain an amplification coefficient of one rod equal to 3 and provide a yield energy of 25—30 joules from one specimen. Connecting the rods		SOURCE: Optiko mekhanicheskaya promyshlennost', no. 6, 1966, 46
light pulse was obtained by the use of neodymium glass rods. Cylindrical specimens of glass (45 mm in diameter and 250 mm long) activated with neodymium were connected in series-parallel. Each specimen was optically pumped by six direct pulse lamps placed in a multielliptical illuminator. The laser consisted of two identical channels, each containing three rods assembled on one axis. Q-modulation was done by two prisms fixed on a common shaft rotating at 18,000 rpm. The light diameter of the prism (30 mm) was coordinated with the light diameter of the operating rod by means of a Galileian tube. The experiments showed that for effective pumping of an operating body 45 mm in diameter the content of Nd ₂ O ₃ should not exceed 4%. In this way it is possible to obtain an amplification coefficient of one rod equal to 3 and provide a yield energy of 25—30 joules from one specimen. Connecting the rods	light pulse was obtained by the use of neodymium glass rods. Cylindrical specimens of glass (45 mm in diameter and 250 mm long) activated with neodymium were connected in series-parallel. Each specimen was optically pumped by six direct pulse lamps placed in a multielliptical illuminator. The laser consisted of two identical channels, each containing three rods assembled on one axis. Q-modulation was done by two prisms fixed on a common shaft rotating at 18,000 rpm. The light diameter of the prism (30 mm) was coordinated with the light diameter of the operating rod by means of a Galileian tube. The experiments showed that for effective pumping of an operating body 45 mm in diameter the content of Nd ₂ O ₃ should not exceed 4%. In this way it is possible to obtain an amplification coefficient of one rod equal to 3 and provide a yield energy of 25—30 joules from one specimen. Connecting the rods		TOPIC TAGS: solid state laser, laser emission, neodymium glass
	Card 1/2 UDC: 621.378.324:621.376		ABSTRACT: An investigation was made of a laser in which high emission energy of the light pulse was obtained by the use of neodymium glass rods. Cylindrical specimens of glass (45 mm in diameter and 250 mm long) activated with neodymium were connected in series-parallel. Each specimen was optically pumped by six direct pulse lamps placed in a multielliptical illuminator. The laser consisted of two identical channels, each containing three rods assembled on one axis. Q-modulation was done by two prisms fixed on a common shaft rotating at 18,000 rpm. The light diameter of the prism (30 mm) was coordinated with the light diameter of the operating rod by means of a Galileian tube. The experiments showed that for effective pumping of an operating body 45 mm in diameter the content of Nd ₂ O ₃ should not exceed 4%. In this way it is possible to obtain an amplification coefficient of one rod equal to 3 and provide a yield energy of 25-30 joules from one specimen. Connecting the rods

L-29565-66 ACC NR: AP6018895 0 in series reduces the amplification of optical pumping, owing to the appearance of free generation of the whole channel. This difficulty can be eliminated by introducing, between the rods, optical decoupling filters made of uranyl glass. The filters, together with the operating rods, are placed in the laser illuminators and are pumped simultaneously with the rod. The optical density of the filter is selected in such a way that at maximum pumping no free generation appears in the laser channel: when the filters are illuminated at the moment when maximum Q for the resonator is reached, one light pulse is generated. By introducing optical decoupling, emission with an energy of 90 joules at 10^{-7} sec duration was obtained from one channel of the laser. The angular distribution of generated radiation improves as the optical pumping increases. Synchronous inclusion of two laser channels was obtained by appropriate adjustment of the laser elements. The time spread of the pulses emitted by both channels did not exceed 10-8 sec. With the simultaneous inclusion of two channels, a light pulse with an energy of 180 joules (corresponding to an emission intensity of 1.5 to 2 hw) was generated. 20/ SUBM DATE: 07Apr66/ ORIG REF: 001/ ATD PRESS:5 1/6 Card



 ZHO	ULH 16	E 4, 1+ 211										
CHOKIN,	Sh. Ch.;	KIKTENKO,	V.A.;	ZHULAY	EV, A.Z	h.	الخاء					
	Basic in	ndices and Kazakhstan	compar	ative e	valuat:	ion	of vari	ants	of	the Ir	tysh-	
•	D 157.	wasaring val					1,	DOK	נו	HO.12:	3-15 11:1)	
				(Kazaki	nstan(Cana)	LB)					
									1			
		tropical Description										
							is the second					
									į		100	
					er jarek er er er er	4 10	11					

Z	HULAYEV, A.Zh						
	Device nain	g a calorimet Izv. AN Kaz	er for doter akh, SSR, Se	mining the	amount of	ice gruel	
		(Hydraulic	engineering	—Instrumen	(HIRA its)	14:12)	




Ev, A.Zh.,									
water in '60.	tal determ turbulent	ination motion.	of the in Vest.Al	ntensity V Kazaki	7 of cr	ystalli 16 no.	zation 3:51-5	of } W-	
	(Ice)					(MIRA	13:6)	
	* 1								
					- 30				
									1 - 1 - 2
					1000				
								1 1	
	in the engli								
					110				
				1					
						4, 4,			
							1		
									李田子 医奎宁

ZHULAYEY, A. ZH.

Zhulayev, A. Zh.

"The Process of Cooling of Non-Freezing Streams (Mountain Rivers)." Acad Sci Kazakh SSR. Inst of Power Engineering. Alma-Ata, 1955. (Dissertation for the Degree of Candidate in Technical Sciences).

SO: Knizhnaya Letopis', No 27, 2 July 1955




ZHULAYEV R.Zh., kand.tekhn.nauk, otv.red.; VELIKANOV, M.A., red.;
DEMENT YKV, M.A., prof., doktor tekhn.nauk, red.; DUMITRASHKO,
N.V., doktor geograf.nauk, red.; KAVETSKIY, S.F., kand.geograf.
nauk, red.; KOCHERGA, F.K., kand.sel'skokhoz.nauk, red.; CHOKIN,
Sh.Ch., akademik, red.; OSADCHIY, F.Ya., red.; ROROKINA, Z.P.,
tekhn.red.


[Materials of the Fourth All-Union Conference on Torrential Floods]
Materialy IV Vsesoiusnoi konferentsii po selevym potoksm. Alma-Ata.
1959. 231 p. (MIRA 12:10)


1. Akademiya nauk Kazekhskoy SSR, Alma-Ata. Institut energetiki.
2. Akademiya nauk Kazekhskoy SSR (for Zhulayev, Chokin). 3. Chlen-korrespondent AN SSSR (for Velikanov). 4. Vsesoyusnyy nauchno-issledovatel skiy institut gidrotekhniki (for Dament yev). 4. Sredne-aziatskiy nauchno-issledovatel skiy institut lesnogo khozyaystva (for Kocherga).


(Floods--Congresses)

APPROVED FOR RELEASE: 07/16/2001 CIA-RDP86-00513R002065010016-0"











ZHU	LAYEV, RZh.									٠.
	Graphic and	analytic me	thod for cal : no.8:57-66 (Canals)	culating	power	canals (MI	RA (Izv. 3:12)		
			(Augus)							





	FREEE I DOOK EXPLOIMATION SOV/5292 Sovembehantys po priklading genovg dismalas, Alma-Ain, 1956 Thing Sovembehantys po priklading genovg dismalas, a. Alma-Aits, 23-26 oktybryn Alma-Aits, 23-26 octybryn Alma-Aits, 23-26 oktybryn Alma-Aits, 23-26 october 1955) Alma-Aits, 124-40 Ni Narakhing ESH, 1959.	copies printed.	COUNCE: The book consists of the transcriptions of its paper read at the conference on gas dymerical universation in the initiative of the Lambhaity genderarcher which are conversed under the initiative of the Lambhaity genderarcher than a convensed under the initiative of the Lambhaity genderarcher which is a second to the lambhaity conference of the lambhaity of the Analysis of Spinesis and the Initiative of Power Expinesis of the Analysis of Spinesis and the Order 20-5, 1956. Three branches of spinish gast dynamics were discussed, menaly 19-15 for 1 liquids and gasts, servicement of the processes, and the outflow of 1 liquids, it is precised a spinished of the conference consists in the adaptation of theory to methods of technical computation and measuring methods related to industrial a precise and other thankstrial processes in whith servicement photomers play a predominant rule. Eight paper read as the Conference of the missing papers are in 10. Lover (Eneral and Astrophymenic Characteristics of Pairwiffed Coal Fatt, Benness, Daniel Spinish, M. Marinov, Yu. P. Degamor, S.Y. Buldman, T.K. Miromind, A.B. Rettyshory, and G.Y. Tahnkov. E.G. Loytynanity is mentioned as being in ethers of Pairwiffer of Spinyaratiy is mentioned as being in ethers of of degreened (Eastah Sciences, Docesti, M. Marinov, Coaledance of Eastah Sciences, Docesti, M. Marinov, Coaledance of C	as a newber of the same aniversity. Inferences are found at the end of Seaton of October 54, 1956 (North.c.) Animows, G.S. Investigating Durbulence Characteristics of a Prec Sonisothermic Jot and an Open Flanc.	essl.	Dubband, d.v. Regularity of Motion and Combustion of Crait Particles 69 Ranrelbuk, M.M., and H.I., Fol'skiy. On the Oriols in the Tiscois 69 Flow of Gas in a Plane Parallel Chamel. Contents of the Discussion in Brief Essation of October 24, 1996 (Evening) Essation of October 24, 1996 (Evening) Hading of Mifferent American of an Asially Symmetrical Vet of Gas in a	88
--	---	-----------------	--	--	-------	---	----

Transactions of the Conference (Cont.) 501/5290	
Treffrenke, A.T. Investigating a Contrest teted Turkulent Jot Akatrov, K.I., Survey of the Works of the Department of Hydrosaro- dynamics of the Leningrad Polytechnical Institute form Kalluin	es es
on the Jet involy Shepter, 3,P.,, and S. Tsoy. Phane Jot in a Cross Section of an ALT Concist:	308
Despaiows, V.O. Use of Hydrointegrators Por Solving Int Prublems	SE 2
Contents of the Discussion in Brief. Session of October 25, 1996 (Morning)	Si .
Interelison, B.D. [Candidate of Technical Sciences; Decent; Technini'nyy bottourshinyy institut imen Polumora, Leningrad (Central furbice and Botler Institute from Polumora, Leningrad (Central furbice and Jose Problems of the Aerodynamics of Purace Cyclose Chabbers and of the Combine of the Cont Powder Niverised Coul	21
Care 6/9	
France tions of the Conference (Cont.) 80V/5290	
Tetimento, B.P. Candidate of Technical Selectes, Jerodynamics of an Involute Jet, and of a Cyclope Chumber	á
Polkov, Ye. V., Som devolynanic Problem of a Two-Karo Flow in a Cyclose Purace	ឌ្គ
Tunkocogiy, A.V., and I.P. Basina. On the Problem of the Working Process in a Cyclore Chabber	ន្ត
Takabow, G.V., Gezeralising Aerodynanic Laws of Cyclose Charlese	ង ង
Session of October 25, 1976 (Drening)	
Repayaboy, A.B. (Doctor of Technical Sciences; Institut energettki (factitate of Power Engineering)), Uniflow Flame of Palverined Coal	3
relegie, A.3. Regularities of Gas Flone Barning	જુ
Francisculars of the Conference (Cont.) 500/5000	, , , , , , , , , , , , , , , , , , ,
Tershin, 3h. A. Aerodynanies of a Turbulent Gas Flane	Egg.
tobarev, M.T. [familiate of Technical Ecionomi that thing politebackeshy institut term introduce; the familiate term introduce of Employed (1971) in the jame interpretable of Open Hearth Pursace. Technical of New Gas Heads of Open Hearth Pursace.	178
Regionar, te. P. On the Thermal Regine of the Chaffication Process.	菱
Conference of the Universation in Figure 19, 1995	ę
Ebulyev, p. 2], Canlidate of Debital Sciences Describ. Sirwy of forther Mandonales Dom by the Intitut Ferretiki Al MacCa (Intitute of Poer Ergirectic of the Arakmy of Science Vandalaby Sig)	į. Et
Roserento, 5.V. (breaked). India Problem of Flow Thorodynautre In Feel Bounding Carditions	ង

SOV/124-58-8-9010

Translation from: Referativnyy zhurnal, Mekhanika, 1958, Nr 8, p 100 (USSR)

TELESTRESTE CONTROLLES DE CONTROLLES DE LES DE LES

· AUTHOR: Zhulayev, R.Zh.

TITLE:

Calculating the Quantity of Alluvium Entrapped by a Slit-type Sand-and-gravel Trap (Raschet zakhvata nanosov v shchelevuyu pesko-graviyelovku)

PERIODICAL: Izv. AN KazSSR. Ser. energ., 1956, Nr 11, pp 18-33

ABSTRACT:

Designs are examined of atmospheric galleries wherein the water and alluvium flow in freely through a slit in the bottom of the flow channel. The slit spans the width of the main channel, being normal to the main direction of flow. Similarity criteria are selected; differential equations of motion are set up, and results are given of some experiments. The author adduces in a general form a formula for calculating the quantity of suspended alluvium that is entrapped by the slit. Several conclusions are drawn and proposals made, amongst which: 1) The use of pressure in the gallery is considered undesirable; 2) mention is made of the importance of certain nondimensional similarity parameters in determining the motion both of the alluvium suspended in the water and of that which drifts along

Card 1/2

SOV/124-58-8-9010

Calculating the Quantity of Alluvium Entrapped (cont.)

the bottom; 3) it is asserted that increasing the width of the slit [Note: as opposed to a reference width] increases the quantity of alluvium that the slit entraps and increases also, of course, the amount of alluvium-bearing water that it diverts from the main flow. The author remarks that the wastefulness of such a procedure (particularly where there is little or no water to spare for diverting the alluvium and then flushing it away) necessitates an improvement in the design of the slit, and especially in that of the "supplementary chamber" (which separates the alluvium from the water) and of the "bottom guide baffles" which concentrate the zone of active entrainment of the alluvium and thereby reduce the amount of water needed to flush the alluvium away. The paper includes an account of methods for approaching the problem of estimating the quantity of alluvium that may be expected to be entrapped by a slit of given design. The insufficient number of numerical values given in the paper for various of the coefficients involved makes it difficult to attempt any specific calculation of a slit-type sand-and-gravel trap.

M.S. Vyzgo

Card 2/2

8(6), 14(6)

SOV/112-59-2-2689

Translation from: Referativnyy zhurnal. Elektrotekhnika, 1959, Nr 2, p 58 (USSR)

AUTHOR: Arykova, A. I., Zhulayev, R. Zh., and Sugurov, Sh. P.

TITLE: Major Shortcomings in the Operation of Small Mountain Hydroelectric Generating Stations of Kazakhstan and Measures for Eliminating Them (Osnovnyye nedostatki raboty malykh gornykh GES Kazakhstana i puti ikh ustraneniya)

PERIODICAL: Izv. AN Kazakhskaya SSP. Ser. energ., 1957, Nr 1(12), pp 17-26 (summary in Kazakh)

ABSTRACT: A survey of over 40 hydroelectric generating stations in southern districts can substantiate the following general characterization of their operating conditions: (1) most stations have no engineering-type water intakes; (2) there is almost no silt control; (3) nearly all stations experience great difficulties during the winter period; (4) most stations have construction and layout of hydraulic structures which do not meet requirements of mountain

Card 1/2

SOV/112-59-2-2689

Major Shortcomings in the Operation of Small Mountain Hydroelectric...

streams. Major design shortcomings are: (1) unlucky selection of site of many hydroelectric generating stations; (2) inadequate allowance for long-range development of the district; (3) imperfect construction and layout of water intakes, settlers, spillway structures, and headwater reservoirs; (4) assigned low stream speeds in channels insufficient for frazil-ice removal. Major causes of inadequate operation of the stations are: (1) relatively low engineering qualifications of the service personnel; (2) absence of proper supervision and technical guidance; (3) absence of operating instructions, etc. Ways of eliminating the above shortcomings are suggested.

Yu.M.S.

Card 2/2